Line Isolation Monitor – Remote Annunciator - Model SR-1

Model SR-1 wall mounted remote with Red, Green and Yellow LED lamps with a sonalert audible alarm and silence switch, mounted on a pre-polished stainless steel one gang flush plate. (Specifications for the SR-1)

Remote Annunciator - SR-1 - Specifications

SYM	DESCRIPTION	QTY
1	STAINLESS STEEL MOUNTING PLATE, 1 GANG	1
2	MOUNTING SCREWS	2
3	SR REMOTE ANNUNCIATOR	1

SAFE   SILENCE   HAZARD

ISOLATED POWER SPECIALIST

SENTRY 5
LINE ISOLATION MONITOR REMOTE INDICATOR

PUSH TO
SILENCE

FRONT VIEW

CONTRACTOR'S WIRING MUST
BE MADE WITH UL APPROVED
300 VOLT #18 THHN OR EQUAL

CONNECT TO MATCHING
TERMINALS IN ISOLATED
POWER PANEL L.I.M. SIGNALS
ARE LOW VOLTAGE +5VDC

RED   BLACK   BLUE

J1
+5V   ALARM

GND

TP2
LOUD   SOFT
BEEPER

TP1
ON   OFF
BEEPER

WIRING DIAGRAM

TOTAL REQUIRED

NOTES:

1) CONTRACTOR WIRING THHN OR MTW MINIMUM 18 GA.

FOR:

UNLESS OTHERWISE SPECIFIED	DWN DDS 11-27-14	Isolated Power Specialist	
DIMENSIONS ARE IN INCHES. TOLERANCES: FRACTIONS +- 1/64" ANGLES +- 1/2" DECIMALS .XX +- .01 .XXX +- .05 HOLES .000-.249 DIA. +.005 -.002 .250 .400 DIA. -.008 .003	CHK	TITLE	
	CNC	MODEL# SR-1	
	GA	SIZE C CAGE NO.	DWG NO. 1422-411
	S.O.	SCALE NONE	SHEET 1 OF 1